

# VD-2W Series



2W 2:1 Regulated Single & Dual output

## Features

- Wide 2:1 Input Range
- Full SMD Technology
- 1500 VDC Isolation, Up to 3500 VDC
- Continuous Short Circuit Protection
- Efficiency up to 78%
- -40 ~ 85°C Operation Temperature Range
- Metal Case Standard, Optional Plastic Case



The VD series is a family of cost effective 2.0W single & dual output DC-DC converters. These converters are consisted with Nickel-coated copper in a 24-pin DIL package with high performance features such as 1500 VDC ~ 3500VDC input/output isolation voltage, continuous short circuit protection with automatic restart and tight line / load regulation. Devices are encapsulated using flame retardant resin. Input voltages of 12, 24 and 48 with output voltage of 3.3, 5, 9, 12, 15, 24,  $\pm 3.3$ ,  $\pm 5$ ,  $\pm 9$ ,  $\pm 12$ ,  $\pm 15$  and  $\pm 24$  Vdc. High performance features include high efficiency operation up to 75% and output voltage accuracy of  $\pm 1\%$  maximum.

All specifications typical at  $T_a=25^\circ\text{C}$ , nominal input voltage and full load unless otherwise specified

OUTPUT SPECIFICATIONS	
Voltage accuracy	$\pm 1\%$
Line regulation	$\pm 0.5\%$
Load regulation	$\pm 0.5\%$
	(Output 3.3V / $\pm 3.3$ V Model) $\pm 1.5\%$
Ripple & noise(20 MHz bandwidth)(1)	60mV pk-pk
Short circuit protection	Indefinite(Automatic Recovery)
Temperature coefficient	$\pm 0.02\%/^\circ\text{C}$
Capacitor load(2)	See table

INPUT SPECIFICATIONS	
Voltage Range	See table
Max. Input Current	See table
No-Load Input Current	See table
Input Filter	PI Type
Input Reflected Ripple Current(3)	35mA pk-pk

GENERAL SPECIFICATIONS	
Efficiency	See table, typ.
I/O Isolation Voltage(3 sec)	
Input/Output	1500~3500Vdc
Metal Case/Input & Output	1000Vdc
I/O Isolation Capacitance	500 pF, typ.
I/O Isolation Resistance	1000M Ohm
Switching Frequency	266kHz, typ.
Humidity	95% rel H
Reliability Calculated MTBF(MIL-HDBK-217 F)	>1.121 Mhrs
Safety Standard : (designed to meet)	IEC 60950-1

PHYSICAL SPECIFICATIONS	
Case Material	Nickel-coated Copper
	Non-conductive Black Plastic(UL94V-0 rated)
Base Material	Non-conductive Black Plastic(UL94V-0 rated)
Pin Material	$\varnothing 0.5\text{mm}$ Brass Solder-coated
Potting Material	Epoxy (UL94V-0 rated)
Weight	17.0g(Metal Case)/13.5g(Plastic Case)
Dimensions	1.25"x0.8"x0.4"

ENVIRONMENT SPECIFICATIONS	
Operating Temperature	-40°C~85°C(See Derating Curve)
Maximum Case Temperature	100°C
Storage Temperature	-40°C~125°C
Cooling	Nature Convection



ABSOLUTE MAXIMUM RATINGS(4)	
These are stress ratings. Exposure of devices to any of these conditions may adversely affect long-term reliability.	
Input Surge Voltage(100mS)	
12 Models	24 Vdc, max.
24 Models	40 Vdc, max.
48 Models	80 Vdc, max.
Soldering Temperature	260°C, max.
(1.5mm from case 10sec. max.)	

EMC SPECIFICATIONS		
Radiated Emissions	EN55022	CLASS A
Conducted Emissions (5)	EN55022	CLASS A
ESD	IEC 61000-4-2	Perf. Criteria A
RS	IEC 61000-4-3	Perf. Criteria A
EFT (6)	IEC 61000-4-4	Perf. Criteria A
Surge (6)	IEC 61000-4-5	Perf. Criteria A
CS	IEC 61000-4-6	Perf. Criteria A
PFMF	IEC 61000-4-8	Perf. Criteria A

The information and specifications contained in this data sheet are believed to be correct at time of publication. However, MOTIEN Technologies accepts no responsibility for consequences arising from printing errors or inaccuracies. Specifications are subject to change without notice. No rights under any patent accompany the sale of any such product(s) or information contained herein.

## VD - 2W 2:1 Regulated Single & Dual output

### PART NUMBER STRUCTURE



## MODEL SELECTION GUIDE

MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current		EFFICIENCY @FL(%)	Capacitor Load(uF)
		No-Load (mA)	Full Load (mA)		Min. load (mA)	Full load (mA)		
VD-123R3S2	9-18	30	223	3.3	0	600	74	680
VD-1205S2	9-18	30	222	5	0	400	75	680
VD-1209S2	9-18	30	219	9	0	222	76	330
VD-1212S2	9-18	30	219	12	0	167	76	220
VD-1215S2	9-18	30	219	15	0	133	76	100
VD-1224S2	9-18	30	219	24	0	83	76	33
VD-123R3D2	9-18	30	229	±3.3	0	±300	72	±330
VD-1205D2	9-18	30	219	±5	0	±200	75	±330
VD-1209D2	9-18	30	219	±9	0	±111	76	±100
VD-1212D2	9-18	30	219	±12	0	±83	76	±47
VD-1215D2	9-18	30	219	±15	0	±67	76	±33
VD-1224D2	9-18	30	219	±24	0	±42	76	±22
VD-243R3S2	18-36	20	109	3.3	0	600	76	680
VD-2405S2	18-36	20	107	5	0	400	78	680
VD-2409S2	18-36	20	107	9	0	222	78	330
VD-2412S2	18-36	20	107	12	0	167	78	220
VD-2415S2	18-36	20	107	15	0	133	78	100
VD-2424S2	18-36	20	107	24	0	83	78	33
VD-243R3D2	18-36	20	112	±3.3	0	±300	74	±330
VD-2405D2	18-36	20	109	±5	0	±200	76	±330
VD-2409D2	18-36	20	107	±9	0	±111	78	±100
VD-2412D2	18-36	20	107	±12	0	±83	78	±47
VD-2415D2	18-36	20	107	±15	0	±67	78	±33
VD-2424D2	18-36	20	107	±24	0	±42	78	±22
VD-483R3S2	36-72	12	56	3.3	0	600	74	680
VD-4805S2	36-72	12	56	5	0	400	75	680
VD-4809S2	36-72	12	56	9	0	222	75	330
VD-4812S2	36-72	12	56	12	0	167	75	220
VD-4815S2	36-72	12	56	15	0	133	75	100
VD-4824S2	36-72	12	56	24	0	83	75	33

Suffix "H" means 3.5KVdc isolation

Suffix "P" means Plastic case instead of standard Metal Case

## VD - 2W 2:1 Regulated Single & Dual output

MODEL NUMBER	INPUT Voltage Range (Vdc)	INPUT Current		OUTPUT Voltage (Vdc)	OUTPUT Current		EFFICIENCY @FL(%)	Capacitor Load(µF)
		No-Load (mA)	Full Load (mA)		Min. load (mA)	Full load (mA)		
VD-483R3D2	36-72	12	56	±3.3	0	±300	74	±330
VD-4805D2	36-72	12	56	±5	0	±200	75	±330
VD-4809D2	36-72	12	56	±9	0	±111	75	±100
VD-4812D2	36-72	12	56	±12	0	±83	75	±47
VD-4815D2	36-72	12	56	±15	0	±67	75	±33
VD-4824D2	36-72	12	56	±24	0	±42	75	±22

Suffix "H" means 3.5KVdc isolation

Suffix "P" means Plastic case instead of standard Metal Case


### NOTE

1. Ripple/Noise measured with a 1µF ceramic capacitor.
2. Test by nominal input voltage and constant resistor load.
3. Measured Input reflected ripple current with a simulated source inductance of 12µH.
4. Exceeding the absolute ratings of the unit could cause damage. It is not allowed for continuous operating.
5. Input filter components are required to help meet conducted emission class A, which application refer to the EMI Filter of design & feature configuration.
6. An external filter capacitor is required if the module has to meet IEC 61000-4-4 and IEC 61000-4-5.  
The filter capacitor Motien suggest: Nippon - chemi - con KY series, 220µF/100V.

### TEST CONFIGURATIONS


#### Input Reflected Ripple Current Test Step

Input reflected ripple current is measured through a source inductor  $L_{in}$  (12µH) and a source capacitor  $C_{in}$  (47µF, ESR<1.0Ω at 100KHz) at nominal input and full load.




#### Output Ripple & Noise Measurement Test

Use a capacitor  $C_{out}$  (1.0µF) measurement. The Scope measurement bandwidth is 0-20MHz.




#### EMI Filter

Input filter components ( $C_1$ ,  $L$ ) are used to help meet conducted emissions requirement for the module. These components should be mounted as close as possible to the module; and all leads should be minimized to decrease radiated noise.




C1	L
100µF, 100V	12µH




12 Models

VD - 2W 2:1 Regulated Single & Dual output




24 Models



48 Models

MECHANICAL SPECIFICATIONS




24 Pin DIL Package  
Nickel-Coated Copper

- Notes: All dimensions are typical in millimeters ( inches ).
1. Pin diameter:  $0.5 \pm 0.05$  (  $0.02 \pm 0.002$  )
  2. Pin pitch and length tolerance:  $\pm 0.35$  (  $\pm 0.014$  )
  3. Case Tolerance:  $\pm 0.5$  (  $\pm 0.02$  )

PIN CONNECTIONS		
PIN NUMBER	SINGLE	DUAL
2	-V Input	-V Input
3	-V Input	-V Input
9	N.P.	Common
11	N.C.	-V Output
14	+V Output	+V Output
16	-V Output	Common
22	+V Input	+V Input
23	+V Input	+V Input

(The Pin Connection of high isolation one is the same with normal one.)

MECHANICAL SPECIFICATIONS



For "P" Case  
24 Pin DIL Package  
Non-Conductive Plastic

- Notes: All dimensions are typical in millimeters ( inches ).
1. Pin diameter:  $0.5 \pm 0.05$  (  $0.02 \pm 0.002$  )
  2. Pin pitch and length tolerance:  $\pm 0.35$  (  $\pm 0.014$  )
  3. Case Tolerance:  $\pm 0.5$  (  $\pm 0.02$  )

PIN CONNECTIONS		
PIN NUMBER	SINGLE	DUAL
2	-V Input	-V Input
3	-V Input	-V Input
9	N.P.	Common
11	N.C.	-V Output
14	+V Output	+V Output
16	-V Output	Common
22	+V Input	+V Input
23	+V Input	+V Input

(The Pin Connection of high isolation one is the same with normal one.)